PROCEEDINGS OF ISAP '92, SAPPORO, JAPAN

COMPARISON OF OPTIMIZATION PROCEDURES FOR RADAR SCATTERING MATRICES

Wolfgang-Martin Boerner¹, Xin Zhang¹, Chuan-Li Liu¹,

Hyo-Joon Eom^2 , Yoshio Yamaguchi³ and Mitsuro Tanaka⁴

UNIVERSITY OF ILLINOIS AT CHICAGO UIC-EECS/CSL, M/C 154, 840 W. TAYLOR ST., SEL-4210 CHICAGO, IL/USA-60680-4348, T/F: +[1](312)996-5480/2456

²KOREA ADVANCED INSTITUTE OF SCIENCE AND TECHNOLOGY KAIST-KIT/EML, 400 KUSUNG-DONG, YUSUNG-GU TAE-JON.SHI 300-31 KOREA, T/F: +[82](42)829-3436/861-5636

³NIIGATA UNIVERSITY, ENGINEERING FACULTY NU-EF/EIE, IKARASHI 2 NOCHO 8050 NIIGATA-SHI, 950-21 JAPAN, T&F: +[81](25)262-6752

⁴OITA UNIVERSITY, ENGINEERING FACULTY OU/EF, Electrical and Electronic Engineering, 700 Dannohama OITA-SHI, 870-11 JAPAN, F/T: +[81](975)67-2290/69-3311x796

1. INTRODUCTION

Basic principles of radar polarimetry are introduced and various optimization procedures for the propagation (scattering) range operator equation and the received power are presented and compared. It is assumed that the radar is a complete coherent dual orthogonal (A,B) transmit/receive antenna system of high channel isolation and antenna side-lobe reduction, where in the case of wave interaction with a discrete stationary point target the propagation (scattering) matrix is given by the 2x2 coherent Jones (Sinclair) matrix [S(A,B)], the 2x2 complex Graves power [G(AB)], the 3x3 or 4x4 complex covariance matrix [$\Sigma(A,B)$], and/or the 4x4 real Mueller (Kennaugh) power density matrix [M] for the symmetric (monostatic reciprocal: $S_{AB} = S_{BA}$) or the asymmetric (general

bistatic, monostatic non-reciprocal: $S_{AB} \neq S_{BA}$) cases, respectively. Four di-

stinctly separate optimization procedures are here introduced for the symmetric case, demonstrating that for the coherent (deterministic) scattering scenario the solutions obtained from optimizing the pertinent power density expressions associated with either [S(A,B)],[G(AB)],[Σ (A,B)] and/or [M] are identical, and so approximately also for the partially polarized case, whereas for the partially coherent case more elaborate optimization procedures for the 3x3 covariance and/or 4x4 Mueller matrices need to be employed utilizing special properties of Lie group SU(n = 2,3,4) expansions, i.e., the 2x2 Pauli spin [σ_i ,

i = 0,1, 2,3], the 3x3 Hausdorff (Gell-Mann)[σ_i , i = 1,2,...8] and the 4x4 Dirac [θ_i , i = 0,1,2,...15] matrices.

It is shown that there exist in total five unique pairs of characteristic polarization states for the symmetric coherent scattering matrix [S(A,B)] of which two pairs, corresponding to the cross-polarization (x-pol) null and co-polarization (co-pol) maxima, are identical; whereas the x-pol max and x-pol saddle point pairs are distinct. These three pairs of orthogonal characteristic polarization states are also mutually at right angles to one another on the polarization sphere. The fifth pair, the (in general) non-orthogonal co-pol null pair, lies in the plane spanned by the co-pol max, or equivalently the x-pol

null, and the x-pol max pairs which determine the 'target characteristic plane (circle) of Kennaugh' and the angle between the co-polar nulls is bisected by the line joining the two co-pol maxs; and together with the orthogonal x-pol saddlepoint pair, being at right angles to this plane, they re-establish Huynen's 'polarization fork' concept. The distinctly different optimization approaches are compared by one illustrative example in which, besides the 'polarization forks', also the co-pol and x-pol power density plots and the relative co/cross-polarization phase (polarimetric correlation coefficient) plots are presented.

Based on this complete description of isolated and distributed scatterers, polarimetric target classification, target-versus-clutter discrimination, and optimal contrast enhancement algorithms are derived and shown to be of great utility in the proper interpretation of POL-RAD/SAR microwave signatures in terrestrial and planetary remote sensing.

2. OVERVIEW

The basic principle of radar polarimetry is based on the concept of characteristic polarization states first introduced by Kennaugh [1], who demonstrated that there exist radar polarization states for which the radar receives minimum /maximum power. This min/max polarization state theory was extended primarily by Huynen[2], who introduced the "polarization fork" concept, and more recently by us [3-10] and at DLR-Oberpfaffenhofen [11]. With the advent of dual polarization coherent radar [12] and Pol-SAR [13] systems, radar polarimetry has become a subject of recurring and globally intensifying interest in recent years [14-16]. Inspite of extensive studies of this theory, a final rigorous and complete formulation still is warranted [4]. Different approaches were introduced for determining these characteristic polarization states by using the voltage equation eigenvalue problem of the scattering matrix [1,2], the basis transformation techniques [3,6,7], the three-stage procedure for the complex Graves power matrix [3,5], the Mueller matrix approach for the "degenerate coherent Stokes vector case" [8,9], and more recently, the polarimetric co-variance matrix optimization procedure [10,11]. All of these methods are compared and it is shown how each of them contributes partially towards a complete understanding of coherent scattering matrix properties. More approaches still may be required to completely resolve all unanswered questions even for the coherent case, for example, such as those recently presented in [16] for applications to radar meteorology; and a more rigorous group-theoretic approach of optimizing the Sinclair, covariance, and Mueller matrices expanded in terms of Lie (SU(2), SU(3), SU(4/2)) groups associated with the Pauli spin matrices as pursued vigorously by Cloude [16]. Whereas, a unique optimization method for the general partially coherent case still does not exist, considerable progress was made in determining an optimization approach for the partially polarized case [4,8,10, 16] for which it is assumed that the wave incident on a stochastic scatterer is completely polarized. Also, it is shown in [10] that there exist 'physical realizability' conditions to which the elements of the 4x4 Mueller matrices are subjected in order to identify erroneous measurement results such as of scattered waves with degree of polarization greater than unity [16]. These and similar 'physical realizability' conditions apply, in general, also in the partially polarized case requiring a four-dimensional polarization sphere treatment together with a SU(4/2) group-theoretic treatment especially for the general asymmetric matrix cases, which will be considered in another forthcoming paper [10]. Finally, optimal contrast enhancement algorithms are intro-duced [10,17] and applied to optimal image feature extraction in POL-RAD/SAR image interpretation [18,19].

3. INTERRELATION OF SCATTERING MATRICES

- a) 2x2 coherent (complex) Sinclair matrix [S(AB)], $\vec{E}_{s}(AB) = [S(AB)]\vec{E}_{i}(AB)$, [S(AB)] = $\begin{bmatrix} S_{AA} & S_{AB} \\ S_{BA} & S_{BB} \end{bmatrix}$ with $\vec{E}(AB)$ denoting electric field vector;
- b) 2x2 hermitian (complex) Graves matrix [G(AB)], [G(AB)] = [S(AB)]⁺[S(AB)] with { }⁺ denoting hermitian conjugate;
- c) 3x3 hermitian (complex) Covariance matrix [$\Sigma(AB)$] [$\Sigma(AB)$] = $\vec{Q}(AB)\vec{Q}(AB)^{+}$, $\vec{\Omega}(AB = BA)^{T} = (S_{AA} \quad \sqrt{2}S_{BB} \quad S_{BB})$ with {}^T denoting transpose of covariance feature vector $\vec{Q}(AB = BA)$, satisfying $||\vec{\Omega}||^{2} = \text{Span}[S(AB)] = |S_{AA}|^{2} + 2|S_{AB}|^{2} + |S_{BB}|^{2}$;
- d) 4x4 real Mueller power density matrix [M], g_s = [M]g_i with [M] = [A(AB)]([S(AB)]@[S(AB)]^{*})[A(AB)]⁻¹ where [A(AB)] denotes the 4x4 Kronecker expansion matrix with @ denoting tensorial matrix multiplication, and g_{s,i} representing the scattered (s) and incident (i) Stokes vectors.

4. REFERENCES

- [1] E.M. Kennaugh, "Effects of Type of Polarization on Echo Characteristics", The Ohio State University, Antennas Laboratory, Columbus, OH, Rpts 381-1 to 394-24,1949-1954, and <u>Rpt 389-12 (M.Sc. Thesis: March 1952)</u> in particular.
- [2] J.R. Huynen, "Phenomenological Theory of Radar Targets", Ph.D. dissertation, Rotterdam: Drukkerij Bronder-Offset N.V., 1970 (also see: ibid, dissertation up-date, in P.L.E. Uslenghi, ed, <u>Electromagnetic Scattering</u>, New York: Academic Press, 1978, pp 653-712).
- [3] W.M. Boerner, "Use of Polarization Dependence in Electromagnetic Inverse Scattering", <u>Radio Science</u>, Vol. 16(6) (Special issue including papers: 1980 Munich Symp. on Em Waves), pp. 1037-1045, Nov/Dec. 1981 (also see: ibid et al, <u>IEEE Trans Ant & Propag.</u>, Vol. AP-29, pp. 262-271, 1981).
- [4] W-M. Boerner, W-L. Yan, A-Q. Xi and Y. Yamaguchi, On the Basic Principles of Radar Polarimetry: The Target Characteristic Polarization State Theory of Kennaugh, Huynen's Polarization Fork Concept, and its Extension to the Partially Polarized Case, <u>IEEE Proc, Vol. 79, No. 10</u>, pp. 1538-1550, Oct. 1991.
- [5] A.B. Kostinski and W-M. Boerner, "On Foundations of Radar Polarimetry", IEEE Trans. A&P, Vol. AP-34, No. 12, Dec 1986, pp. 1395-1404 1470-1473.
- [6] A.P. Agrawal and W-M. Boerner, "Redevelopment of Kennaugh's Target Characteristic Polarization State Theory Using the Polarization Transformation Ratio Formalism for the Coherent Case", <u>IEEE Trans. A&P, Vol AP-27, No. 1</u>, pp. 2-14, Jan 1989.
- [7] W-M. Boerner and A-Q. Xi, "The Characteristic Radar Target Polarization State Theory for the Coherent Monostatic and Reciprocal Case Using the Generalized Polarization Transformation Ratio Formulation", <u>AEÜ</u>, Vol. 44,

No. 4, pp. 273-281, July/Aug. 1990.

- [8] W-L. Yan and W-M. Boerner, "Optimal Polarization States Determination of the Stokes Reflection Matrices [M_p] for the Coherent Case, and of the Mueller Matrix [M] for the Partially Polarized Case", <u>Journal of Electro-</u> magnetic Waves and Applications, JEWA Vol. 5, No. 10, pp. 1123-1150, Oct. 1991.
- [9] Y. Yamaguchi, K. Sasagawa, M. Sengoku, T. Abe, W-M. Boerner, W-L. Yan and A-Q. Xi, "Characteristic Polarization States of Coherently Reflected Waves Based on the Stokes Vector Formulation in Radar Polarimetry", Japan Journal for Electr and Commun Engin JIEECE, Vol. AP/90-35, pp 23-30, 1990 July 19.
- [10] W-M. Boerner, C-L. Liu and X. Zhang, A rigorous optimization procedure for alternate co-variance matrix formulations in radar polarimetry, (INVITED), <u>European Telecommunications Journal</u>, Special Issue on Radar Polarimetry, <u>Spring 1992</u>, in completion.
- [11] E. Lüuneburg, V. Ziegler, A. Schroth, K. Tragl, "Polarimetric Covariance Matrix Analysis of Random Radar Targets", NATO-AGARD-EPP Symposium on Target and Clutter Scattering and their effects on Military Radar Performance, Ottawa, Canada, 1991 May 6-10, Proceedings (11 pages) 1991.
- [12] D. Giuli, "Polarization Diversity in Radar", Proc. IEEE, Vol. 74(2), pp. 245-269, Feb. (1986).
- [13] J.J. van Zyl, "On the Importance of Polarization in Radar Scattering Problems", Ph.D. Dissertation, California Inst of Techn, Pasadena, CA, Jan(1986).
- [14] W-M. Boerner, et. al., eds., Inverse Methods in Electromagnetic Imaging, Proc. NATO Advanced Res. Workshop on IMEI, Bad Windsheim, FR. Germany, Sept. 18-24, 1983, NATO-ASI-Series, Series C, Math. & Phys. Sci., Vol. 143, Dordrecht, Holland: D. Reidel Publ. Co., (1985).
- [15] L.W. Root and Matkin, Chairmen/Editors, Proceedings, (Third) Polarimetric (Technology) Workshop, Redstone Arsenal, AL, 1988 August 16-18, GACIAC IIT-RI, 10 W. 35th St., Chicago, IL 60612, (1989).
- [16] W-M. Boerner, et al, eds, Direct and Inverse Methods in Radar Polarimetry, Proc. NATO-ARW-DIMRP (W-M. Boerner, Director), 1988 Sept. 18-24, Bad Windsheim FRG, NATO-ASI-Series C, Math. & Phys. Sci., Vol. C-350, Pts 1&2 (1938 pages), Dordrecht/Boston: D. Reidel Publ. Co., (1992).
- [17] M. Tanaka and W-M. Boerner, "Optimal Antenna Polarization States for Optimal Polarimetric Contract Enhancement for the Mueller matrix cases", Japan Journal for Electronic and Communication Engineering, JIEECE, Vol. AP/92-xy, (24 pages) Summer, 1992.
- [18] W-M. Boerner, B-Y. Foo, and H.J. Eom "Interpretation of the Polarimetric Co-Polarization Phase Term in High Resolution SAR Imaging Using the JPL/ CV-990 Polarimetric L-Band SAR Data", <u>IEEE Trans. on Geoscience & Remote</u> Sensing, Vol. GE-25, No. 1, pp. 77-82, Jan. 1987.
- [19] M. Walther, A.C. Segal and W-M. Boerner, Speckle Reduction in the Development of the Polarimetric Matched Filter (PMIF) for the Optimization of Image Discriminants in POL-SAR Image Analysis, Paper No. VII-8, pp. 1497-1552, in W-M. Boerner, et al, Eds., Proceedings of the NATO-ARW-DIMRP'88, NATO-ASI Series C; Mathematical & Physical Sciences, Vol. C-350, Part 2, D. Reidel Publ. Co., Dordrecht, NL, 1992.